
























**CHIUSURE PNEUMATICHE - PNEUMATIC CLAMPS**

<p><b>Chiusura Pneumatica</b> Pneumatic Clamp</p> <p><b>CPR25</b></p>  <p>Diam. 25mm Clamp. 30Nm Hold. 75Nm Ang. 15-105° Weight. 2,0Kg.</p> <p><a href="#">PDF Catalogue</a></p>	<p><b>Chiusura Pneumatica</b> Pneumatic Clamp</p> <p><b>CPL40</b></p>  <p>Diam. 40mm Clamp. 140Nm Hold. 380Nm Ang. 2-135° Weight. 2,2-2,7Kg.</p> <p><a href="#">PDF Catalogue</a></p>	<p><b>Chiusura Pneumatica</b> Pneumatic Clamp</p> <p><b>CPL50/63</b></p>  <p>EU Norm Diam. 50/63mm Clamp. 250/420Nm Hold. 1.300/1.700Nm Ang. 2,5-135° Weight. 4,0/5,0Kg.</p> <p><a href="#">PDF Catalogue</a></p>	<p><b>Chiusura Pneumatica</b> Pneumatic Clamp</p> <p><b>CPL80</b></p>  <p>EU Norm Diam. 80mm Clamp. 1.000Nm Hold. 2.500Nm Ang. 3-135° Weight. 14Kg.</p> <p><a href="#">PDF Catalogue</a></p>
<p><b>Chiusura Pneumatica</b> Pneumatic Clamp</p> <p><b>CPLV50/63</b></p>  <p>Toll.Comp.(V). 10mm/230mm EU Norm Diam. 50/63mm Clamp. 200/280Nm Hold. 200/280Nm Ang. 2,5-135° Weight. 4,0/5,0Kg.</p> <p><a href="#">PDF Catalogue</a></p>	<p><b>Chiusura Manuale</b> Manual Clamp</p> <p><b>MC</b></p>  <p>HeavyDuty SteelBody Manual Hold. 160Nm Ang. 60-120° Weight. 4,3Kg.</p> <p><a href="#">PDF Catalogue</a></p>	<p><b>Chiusura Pneumatica</b> Pneumatic Clamp</p> <p><b>CPN50/63</b></p>  <p>NAAMS Standard Diam. 50/63mm Clamp. 250/420Nm Hold. 1.300/1.700Nm Ang. 2,5-135° Weight. 4,0/5,0Kg.</p> <p><b>NAAMS</b></p> <p><a href="#">PDF Catalogue</a></p>	<p><b>Chiusura Pneumatica</b> Pneumatic Clamp</p> <p><b>CPN80</b></p>  <p>NAAMS Standard Diam. 80mm Clamp. 1.000Nm Hold. 2.500Nm Ang. 3-135° Weight. 11,5Kg.</p> <p><b>NAAMS</b></p> <p><a href="#">PDF Catalogue</a></p>
<p><b>Chiusura Pneumatica</b> Pneumatic Clamp</p> <p><b>CPR50/63</b></p>  <p>HeavyDuty SteelBody Diam. 50/63mm Clamp. 270/420Nm Hold. 1.000 Ang. 15-120° Weight. 5,0/5,5Kg.</p> <p><a href="#">PDF Catalogue</a></p>	<p><b>Chiusura Pneumatica</b> Pneumatic Clamp</p> <p><b>DL63</b></p>  <p>HeavyDuty SteelBody Diam. 63mm Clamp. 400Nm Hold. 600Nm Ang. 45-90° Weight. 10,0Kg.</p> <p><a href="#">PDF Catalogue</a></p>		

**GRIPPER PNEUMATICI - PNEUMATIC GRIPPERS**

<p><b>Gripper pneumatico</b> Pneumatic Gripper</p> <p><b>B32A/B</b></p>  <p>Diam. 32mm Clamp. 850N/250N Ang. 22,5-160° Weight. 1,3-1,5Kg.</p> <p><a href="#">PDF Catalogue</a></p>	<p><b>Gripper pneumatico</b> Pneumatic Gripper</p> <p><b>B40A/B</b> <b>B40VA/B</b></p>  <p>Diam. 40mm TolleranceComp. (V) Clamp. 1.400/600N Clamp(V). 1.050/460N Ang. 22,5-160° Weight. 2,5Kg.</p> <p><a href="#">PDF Catalogue</a></p>	<p><b>Gripper pneumatico</b> Pneumatic Gripper</p> <p><b>G40.1</b></p>  <p>Diam. 40mm Clamp. 130Nm Hold. 200Nm Ang. 15-105° Weight. 1,8Kg.</p> <p><a href="#">PDF Catalogue</a></p>	<p><b>Gripper per Transfer</b> Transfer Gripper</p> <p><b>G20</b></p>  <p>Diam. 22mm Clamp. 20Nm Hold. 50Nm Ang. 15-90° Weight. 0,8Kg.</p> <p><a href="#">PDF Catalogue</a></p>
---	--	--	--










**DISPOSITIVI DI CENTRAGGIO - LOCATOR DEVICE**

<p><b>Disp. Centraggio</b> Locator Device</p> <p><b>DCP30.1</b></p>  <p>Diam. 30mm Stroke. 20-40mm PushForce. 350N PullForce. 250N RadialForce. 70N AxialTorque. 4Nm Weight. 0,8-1,1Kg.</p> <p><a href="#">PDF Catalogue</a></p>	<p><b>Disp. Centraggio</b> Locator Device</p> <p><b>DCP40</b></p>  <p>Diam. 40mm Stroke. 20-60mm PushForce. 600N PullForce. 500N RadialForce. 150N AxialTorque. 4-6Nm Weight. 1,7-2,0Kg.</p> <p><a href="#">PDF Catalogue</a></p>	<p><b>Disp. Centraggio</b> Locator Device</p> <p><b>DCP63.1</b></p>  <p>Diam. 63mm Stroke. 20-60mm PushForce. 1500N PullForce. 1400N RadialForce. 200N AxialTorque. 4-6Nm Weight. 2,8-3,1Kg.</p> <p><a href="#">PDF Catalogue</a></p>	<p><b>Disp. Centraggio</b> Locator Device</p> <p><b>DCP40</b> (CNOMO STANDARD)</p>  <p>Diam. 40mm Stroke. 25-50mm PushForce. 600N PullForce. 500N RadialForce. 150N AxialTorque. 4-6Nm Weight. 1,7-2,0Kg.</p> <p><b>CNOMO</b></p> <p><a href="#">PDF Catalogue</a></p>
<p><b>Disp. Centraggio</b> Locator Device</p> <p><b>DCPD40W</b></p>  <p>Diam. 40mm Stroke. 20-40mm PushForce. 600N PullForce. 500N RadialForce. 80N Ma. 6Nm Mb. 3Nm Weight. 1,1-1,2Kg.</p> <p><a href="#">PDF Catalogue</a></p>	<p><b>Disp. Centraggio</b> Locator Device</p> <p><b>DCPD63.1</b></p>  <p>Diam. 63mm Stroke. 20-60mm PushForce. 1500N PullForce. 1350N RadialForce. 200N Ma. 60Nm Mb. 30Nm Weight. 3,6-3,8Kg.</p> <p><a href="#">PDF Catalogue</a></p>	<p><b>Disp. Centraggio</b> Locator Device</p> <p><b>DCPD50U</b></p>  <p>Toggle Lock System Diam. 50mm Stroke. 40mm PushForce. 1000N PullForce. 800N RadialForce. 400N Ma/Mb 40/80Nm Weight. 6,7-7,0Kg.</p> <p><a href="#">PDF Catalogue</a></p>	

Cancellare la cache del web browser per essere sicuri di scaricare l'ultima versione dei cataloghi o dei 3Ds / Cancel your web browser cache in order to be sure to download the last release catalogues or 3Ds







**SUBLEVELS - UNDERBODYCLAMPS**

<p>Sublevel UnderbodyClamp <b>DCA50.2</b></p>  <p>SteelBody Diam. 50mm Clamp. 400dN Hold. 470dN HighStrengthPin PinØ. 20-40mm Weight. 5,7Kg.</p> <p><a href="#">PDF Catalogue</a></p>	<p>Sublevel UnderbodyClamp <b>DCA50R.1</b></p>  <p>SteelBody Diam. 50mm Clamp. 250dN Hold. 380dN HighStrengthPin PinØ. 18-40mm Weight. 3,4Kg.</p> <p><a href="#">PDF Catalogue</a></p>	<p>Sublevel Orizzontale Horiz. UnderbodyClamp <b>DCA50Z.1</b></p>  <p>Horizontal LayOut AluBody Diam. 50mm Clamp. 200dN Hold. 330dN HighStrengthPin PinØ. 18-30mm Weight. 3,0Kg.</p> <p><a href="#">PDF Catalogue</a></p>	<p>Sublevel UnderbodyClamp <b>DCA40G</b></p>  <p>LightWeight AluBody Diam. 40mm Clamp. 110dN Hold. 200dN HighStrengthPin PinØ. 16-32mm Weight. 1,8Kg.</p> <p><a href="#">PDF Catalogue</a></p>
<p>Sublevel UnderbodyClamp <b>DCA63V.2/V6</b></p>  <p><b>NEW</b> Toll.Comp (V) 3mm opz.(V6) 6mm Diam. 63mm Clamp. 220-280dN Hold. 330dN HighStrengthPin PinØ. 20-40mm Weight. 7,0Kg.</p> <p><a href="#">PDF Catalogue</a></p>	<p>Sublevel UnderbodyClamp <b>DCA63LxV</b></p>  <p>90° Rotable Hook Toll.Comp.(V). 3mm Diam. 63mm Clamp. 200-280dN Hold. 330dN HighStrengthPin PinØ. 20-40mm Weight. 7,0Kg.</p> <p><a href="#">PDF Catalogue</a></p>	<p>Sublevel UnderbodyClamp <b>DCA63CV</b></p>  <p>SteelBody Pin-Hole Gap Comp. Toll.Comp.(V). 3mm Diam. 63mm Clamp. 220-280dN Hold. 330dN HighStrengthPin Weight. 7,5Kg.</p> <p><a href="#">PDF Catalogue</a></p>	<p>Sublevel UnderbodyClamp <b>DCA63.1</b></p>  <p>HeavyDuty SteelBody Diam. 63mm Clamp. 700dN Hold. 770dN HighStrengthPin PinØ. 20-40mm Weight. 7,3Kg.</p> <p><a href="#">PDF Catalogue</a></p>
<p>Sublevel UnderbodyClamp <b>DPA50</b></p>  <p>SteelBody Diam. 50mm Clamp. 400dN Hold. 470dN Weight. 6,2Kg.</p> <p><a href="#">PDF Catalogue</a></p>			

**RIBALTATORI PNEUMATICI - PIVOT UNITS**

<p>Ribaltatore Pneumatico Pivot Unit <b>RFM.2/RF.2</b></p>  <p>SBI Brake System Hydraulic Control Angles Changeable D. 100-125-160-200 Ang. 15°-129° 190-800Nm (90°)</p> <p><a href="#">PDF Catalogue</a></p>	<p>Ribaltatore Pneumatico Pivot Unit <b>RCM.2/RC.2</b></p>  <p>Angles Changeable Hydraulic Control D. 100-125-160-200 Ang. 15°-129° 190-800Nm (90°)</p> <p><a href="#">PDF Catalogue</a></p>	<p>Ribaltatore Pneumatico Pivot Unit <b>RP80.2</b></p>  <p>Diam. 80 Flat Cylinder Ang. 15-135° 100Nm (90°)</p> <p><a href="#">PDF Catalogue</a></p>	<p>Ribaltatore Elettrico Electric Pivot Unit <b>GRE</b></p>  <p>ServoMotor 400V ServoAxis Controlled Ang. 0-135° Torque: 500Nm Hold: 2.000Nm 3,5 Sec. 0°--&gt;135° Weight: 61Kg.</p> <p><a href="#">PDF Catalogue</a></p>
			<p>Ribaltatore Elettrico Electric Pivot Unit <b>GRE-FESTO</b></p>  <p><b>FESTO</b> ServoMotor 680V ServoAxis Controlled Ang. 0-135° Torque: 500Nm Hold: 2.000Nm 3,2 Sec. 0°--&gt;135° Weight: 47Kg.</p> <p><a href="#">PDF Catalogue</a></p>

**UNITA' LINEARI - LINEAR UNITS - (1/2)**

<p>Unità Lineare Linear Unit <b>SLD.1</b></p>  <p>SBI Lock System 2 Work Positions Stroke Changeable D. 40-50-63-80-125 Stroke. 1-500mm Payload. 40-600Kg. Weight. 9,5-305 Kg.</p> <p><a href="#">PDF Catalogue</a></p>	<p>Unità Lineare Linear Unit <b>SLDS.2</b></p>  <p>Clamps Lock System 2 Work Positions Stroke Changeable Diam. 63-80-125 Stroke. 1-500mm Payload. 150-600Kg. Weight. 54-285 Kg.</p> <p><a href="#">PDF Catalogue</a></p>	<p>Unità Lineare Linear Unit <b>SLG40</b></p>  <p>LightWeight Pin Lock System 2 Work Positions Stroke Changeable Diam. 40 Stroke. 1-300 mm Payload. 25 Kg. Weight. 6,5-9,0 Kg.</p> <p><a href="#">PDF Catalogue</a></p>	<p>Unità Lineare Linear Unit <b>SLCP63</b></p>  <p>Togle Lock System 1 Work Positions Stroke Changeable Diam. 63 Stroke. 5-90 mm Payload. 15 Kg. Weight. 8,0 Kg.</p> <p><a href="#">PDF Catalogue</a></p>
--	---	--	--

UNITA' LINEARI - LINEAR UNITS Continue (2 of 2) ----->


Leeren Sie den Webbrowser-Cache, so können Sie die aktuellste Version der Kataloge oder 3Ds herunterladen / Cancel your web browser cache in order to be sure to download the last release catalogues or 3Ds



**UNITA' LINEARI - LINEAR UNITS - (2/2)**

**Unità Lineare Elettrica**  
Servo Linear Unit

**SLDE**




Servo Unit  
SBI Lock System  
4 Work Positions  
Stroke Changeable  
Sizes. 63-80  
Stroke. 0-500mm  
Payload. 150-250Kg.

[PDF Catalogue](#)

**Unità Lineare Elettrica**  
Servo Linear Unit

**SE80**




ServoMotor 400V  
ServoAxis  
Controlled  
Stroke 0-250mm  
3,0 Sec. 0-250mm  
Stroke 0-500mm  
4,5 Sec. 0-500mm  
Payload. 250Kg.

[PDF Catalogue](#)

**Unità Lineare Elettrica**  
Servo Linear Unit

**SE 3D XYZ**



NEW  
Customized Linear  
Systems 3D XYZ  
ServoMotor  
Controlled  
Example:  
Strokes 500mm  
Payload. 200Kg.

[Info](#)

**MOLTIPLICATORI DI FORZA - FORCE MULTIPLIERS**

**Moltiplicatore di Forza**  
Force Multipliers

**FM100**



SteelBody  
Diam. 100mm  
FwStroke. 50-200mm  
PwStroke. 8mm  
FW Force. 460daN  
PW Force. 4.500daN  
Weight. 20,5-26,5Kg.

[PDF Catalogue](#)

Leeren Sie den Webbrowser-Cache, so können Sie die aktuellste Version der Kataloge oder 3Ds herunterladen / Cancel your web browser cache in order to be sure to download the last release catalogues or 3Ds